

YASH FLOOR TOP-S



Yash Floor Top-S

Emery and quartz based dry shake monolithic concrete floor hardener.

Description

Yash Floor Top-S is a premixed dry shake floor hardener that provides an exceptional hard abrasion resistance for concrete and screed floors. Yash Floor Top-S is formulated from selected graded emery aggregate, cement and special additives to provide a non-oxidizing, dense and smooth surface with high abrasion and wear resistance.

Applications

- Heavy industry.
- Parking areas.
- Warehouses.
- Workshops.
- Service stations.
- Aircraft hangars.
- Loading bays.

Advantages

- High resistance to wearing and abrasion.
- Easy to apply.
- Provides monolithic floor.
- Non oxidizing floor hardener.
- Non-metallic, does not rust.
- Premixed, ready to use.
- Reduces surface dust, and resistant to oil and grease.

Concrete Limitations

The following concrete limitations and properties should be considered to obtain hard concrete surface with high abrasion resistance:

W/C ratio should be less than 0.5, Flocretewater reducing admixtures are highly recommended to achieve such water cement ratio.

Recommended concrete slump between 75 mm to 120 mm.

Cement content should be more than 300 kg/m³.

Proper concrete compaction and leveling is a must.

Method of Use

The right time to spread the Yash Floor Top-S on concrete surface is when light foot traffic leaves an imprint of about 3 - 6 mm.

Any bleed water still present should be removed.

Spread two thirds of the required quantity of Yash Floor Top-S onto the concrete surface and allow the

Technical Properties:

Abrasion resistance	: At least 300 - 500%, improvement, compared to a conventional concrete
Wear resistance	: Class A6
Brinell reading	
Compressive strength (wet cure) mortar consistency	: > 70 MPa @ 28 days
ASTM C109/109M-02	
Hardness	: 8 (Mohs scale)
Colour	: Grey, buff, green & brick red

Material to absorb moisture from concrete.

First floating application should start, when a uniform dark colour appears (indicating material is wet). Either mechanical or manual floating can be used depending on area to be floated and the required finish.

Apply the remaining quantity of Yash Floor Top-S evenly and wait until material becomes wet (darker in colour) before floating.

Use a power trowelling machine to make the final finish. Any wetting of the first or second application of Yash Floor Top-S with water addition will affect the overall quality of the floor.

Proper curing should be maintained to the floor surface as soon as the surface is set and is not be marred by the curing method.

If surface sealing is thought to be necessary, two coats of Strongcoat 173 (epoxy clear floor sealer) or Strongcoat EC10 (epoxy floor coating) can be applied to provide further protection to concrete and steel surfaces.

All expansion joints must be filled with an appropriate sealant. The saw cut construction joints may be filled with Strong coat 104 flexible epoxy resin.

Timing of Application

Timing of Yash Floor Top-S application is critical. Adequate machinery, labor and material should be available to complete the whole area while sufficient concrete moisture is available.

YASH FLOOR TOP-S



Applying Yash Floor Top-S before or after the proper application time can seriously affect the quality of the concrete floor finish.

Application Rate

Yash Floor Top-S should be applied at the following rates:
Medium & Heavy duty floors 3 - 7 kg/m².

Cleaning

All tools should be cleaned immediately after finishing by water.

Packaging

Yash Floor Top-S is available in 25 kg bags.

Storage

Yash Floor Top-S has a shelf life of 12 months from date of manufacture if stored at dry conditions and temperatures between 2°C and 50°C.

If these conditions are exceeded, YASH Technical Department should be contacted for advice.

Cautions

Health and Safety

As Yash Floor Top-S contains Portland cement, Yash Floor Top-S may cause irritation to skin or eyes.

In case of accidental contact with skin or eyes, immediately flush with plenty of water and seek medical advice if necessary.

Fire

Yash Floor Top-S is nonflammable.

More from YASH CONCHEM Products

A wide range of construction chemical products are manufactured by YASH which include:

- Concrete admixtures.
- Surface treatments
- Grouts and anchors.
- Concrete repair.
- Flooring systems.
- Protective coatings.
- Sealants.
- Waterproofing.
- Adhesives.
- Tile adhesives and grouts.
- Building products.
- Structural strengthening.

Note : We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, Yash cannot accept any liability either directly or indirectly arising from the use of Yash products, whether or not in accordance with any advice, specification, recommendation or information given by us.